


90461	HD 7" Quad-View Color Monitor
<p>B1. Features:</p> <ol style="list-style-type: none"> Support 4 HD cameras inputs with different resolution (1080P,720P,PAL,NTSC); Support HDMI and VGA input; Multiple video formats available: 1080P30/1080P25/720P30/720P25/PAL/NTSC Single, dual, triplex, quad, trefoil, Y-split image and PIP display; Touch screen optional; Multi-languages available; Adjustable parking lines available; Five trigger lines and trigger priority available; Support AUTO SCAN, with scan channel and time selectable; Support 60-level manual adjustment with high/low sensitivity selectable, and 3-level automatic adjustment of the LCD backlight; Image adjustable for horizontal, vertical, horizontal - vertical viewing; Wide voltage input: 10 - 32V ; support 12V or 24V automobile battery. 	
<p>B2. Accessories :</p>	
<p>1- Base support bracke 1- U-support bracket 1- Sun shield 4- Angle adjustment screws 1- IR remote control 1- Manual</p>	
<p>B3. Key Specifications:</p>	
<p>LCD size: 7" Resolution: 1024 x 3 (RGB) x 600 Outer dimension 203mm (W) × 112mm (H) × 28mm (T). Power inputs: Automobile storage battery (10-32V) Dot pitch: 0.1506(H) × 0.1432 (V) Contrast: 700:1 Brightness: 600 cd/m² Viewing angle: U: 85° / D: 85°, R/L: 85° / 85° Loudspeaker: one 24*15*4.5mm loudspeaker Audio output: 1W / mixaudio output (maximum 4 camera audio outputs) Operating temperature: -20~+70°C, RH 90% Storage temperature: -30~+80°C, RH 90% Power consumption: MAX 25W Video inputs: 4 Camera Video inputs, Optional: 1 DVI-HDMI/ VGA input Audio inputs: 4 Camera Audio inputs Trigger signal: 5 trigger wires Anti-vibration: 2.1G</p>	